

162-00 ELITE OIL BASE HOUSE PAINT - WHITE

162-00 Elite Oil Base House Paint is the highest quality gloss exterior finish based on proven, durable alkyd resins and refined linseed oils. This product is resistant to fading, yellowing and chalking. It has outstanding brush application with good flow and leveling without sagging. It dries quickly without wrinkling or after-tack.

USES: Use on all painted or primed exterior wood siding, sash and trim and metal.

MATERIAL PREPARATION: Mix well before use.

SURFACE PREPARATION: All surfaces should be dry and cleaned of all dirt, grease, oil, wax and chalk. Old surfaces that are blistering, cracking or peeling should be removed by scraping or burning. All bare wood spots and new wood or hardboard surfaces should be primed with a quality oil or alkyd based exterior primer. Fill nail holes and caulk after priming before applying this product.

APPLICATION: Apply with good enamel brush, roller or by spray. Apply full even coats, always working to a wet edge. Avoid painting in direct sunlight; follow the shade around the house. Do not paint in temperatures below 40°F or above 90°F. Allow adequate ventilation during use.

AIRLESS SPRAY: Use airless equipment capable of maintaining 80-100 lbs input pressure at 28:1 to 30:1 airless pump. Use .017 to .026 inch tips.

162-00

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White
<u>60° GLOSS:</u>	60-75 range
<u>85° SHEEN:</u>	60 max
<u>VEHICLE:</u>	Soya alkyd resins, refined and treated linseed oils and chlorinated paraffin
<u>PIGMENTATION:</u>	Titanium dioxide, EPA approved silicates, factory ground (fade resistant) type pigments. All pigments are free of heavy metals and toxic materials
<u>SOLVENT:</u>	Rule 66 low odor mineral spirits. VOC meets regulation of 380g/L; 3.20 lbs/gal
<u>FLAMMABILITY:</u>	105°F
<u>% VEHICLE SOLIDS (WEIGHT):</u>	36
<u>% PIGMENT (WEIGHT):</u>	38
<u>% SOLVENT (WEIGHT):</u>	26
<u>% TOTAL SOLIDS (WEIGHT):</u>	74
<u>% TOTAL SOLIDS (VOLUME):</u>	56
<u>VISCOSITY:</u>	95-100 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=2.9 dry mils 400 sq.ft/gal=4.0 wet mils=2.2 dry mils 500 sq.ft/gal=3.2 wet mils=1.7 dry mils
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	10.85 lbs.
<u>DRY, SET TO TOUCH:</u>	3 hours
<u>DRY HARD:</u>	24 hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Paint thinner
<u>TYPE OF CURE:</u>	Oxidation
<u>TINTING:</u>	Universal colorants