

177-75 DURA KING OIL BASE GLOSS BARN PAINT

An exterior red paint with fine appearance and good durability giving long life with best protection to the surface. This is a premium product using a house paint vehicle with red pigments of comparable quality that are fade resistant and dry with a full gloss. Can be used for one-coat work over a previously painted surface in good condition.

USES: All wood or metal surfaces on exterior farm buildings; also for residential work.

MATERIAL PREPARATION: Mix well before use.

SURFACE PREPARATION: All surfaces should be dry and cleaned of all dirt, grease, oil, wax and chalk. Old surfaces that are blistering, cracking or peeling should be removed by scraping or burning. All bare wood spots and new wood or hardboard surfaces should be primed with a quality oil or latex based exterior primer. Fill nail holes and caulk after priming and before applying this product.

APPLICATION: Apply with good enamel brush, roller or by spray. Apply full even coats always working to a wet edge. Avoid painting in direct sunlight; follow the shade around the house. Do not paint in temperatures below 40°F or above 90°F. Allow adequate ventilation during use.

AIRLESS SPRAY: Use airless spray equipment capable of maintaining 80-100 lbs. Input pressure at 28:1 to 30:1 airless pump. Use .017 to .026 tips.

177-75

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	Red
<u>60° GLOSS:</u>	20-40
<u>85° SHEEN:</u>	25-45 range
<u>VEHICLE:</u>	Soya alkyd resins, linseed oil
<u>PIGMENTATION:</u>	Red oxide, calcium carbonates. All pigments are free of heavy metals and toxic materials
<u>SOLVENT:</u>	Rule 66 low odor mineral spirits. VOC meets regulation of 380g/L; 3.20 lbs./gal.
<u>FLAMMABILITY:</u>	105°F (combustible)
<u>% VEHICLE SOLIDS (WEIGHT):</u>	30
<u>% PIGMENT (WEIGHT):</u>	40
<u>% SOLVENT (WEIGHT):</u>	30
<u>% TOTAL SOLIDS (WEIGHT):</u>	70
<u>% TOTAL SOLIDS (VOLUME):</u>	56
<u>VISCOSITY:</u>	88-95 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=3.0 dry mils 400 sq.ft/gal=4.0 wet mils=2.2 dry mils 500 sq.ft/gal=3.2 wet mils=1.8 dry mils
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	10.7 - 10.9 lbs.
<u>DRY, SET TO TOUCH:</u>	3 hours
<u>DRY HARD:</u>	24 hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Paint thinner
<u>TYPE OF CURE:</u>	Oxidation
<u>TINTING:</u>	None recommended