

272-SERIES PRO FINISH ZONE MARKING PAINTS

272-series Zone Marking Paint combine the use of a special vehicle with quality pigments to form a tough, durable film with excellent adhesion and wear resistance.

USES: Marking all types of street and floor (concrete surfaces. Ideal for marking parking zones, lanes and shipping docks.

SURFACE PREPARATION: A clean surface is required for best adhesion and durability. Remove dust by brushing off surface with a stiff brush or by scrubbing with water. Remove oil or grease spots with naphtha or turpentine.

APPLICATION: Brush, roller or spray.

DRYING: 10 minutes dust free; non-tracking in 15 minutes. Will vary with temperature and humidity.

272-series

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White, Yellow
<u>60° GLOSS:</u>	5 max (flat)
<u>85° SHEEN:</u>	15 max
<u>VEHICLE:</u>	Soya alkyd copolymer resin
<u>PIGMENTATION:</u>	Titanium dioxide, talc and calcium carbonate. All pigments are free of heavy metals and toxic materials.
<u>SOLVENT:</u>	VMP Naphtha and mineral spirits. VOC meets regulation of 450g/L; 3.80 lbs/gal.
<u>FLAMMABILITY:</u>	57°F. Flammable
<u>% VEHICLE SOLIDS (WEIGHT):</u>	15
<u>% PIGMENT (WEIGHT):</u>	56 (272-00)
<u>% SOLVENT (WEIGHT):</u>	29
<u>% TOTAL SOLIDS (WEIGHT):</u>	71
<u>% TOTAL SOLIDS (VOLUME):</u>	47
<u>VISCOSITY:</u>	77-82 KU
<u>THEORETICAL COVERAGE:</u>	735 square feet per gallon per one mil dry
<u>RECOMMENDED COVERAGE:</u>	200 sq.ft/gal (600 foot stripe-four inches wide)
<u>WEIGHT PER GALLON:</u>	11.7 lbs.
<u>DRY, SET TO TOUCH:</u>	10 minutes
<u>DRY HARD:</u>	3 hours
<u>CLEAN UP SOLVENT:</u>	Paint thinner
<u>TYPE OF CURE:</u>	Oxidation
<u>TINTING:</u>	Not recommended