

280-90 CONCRETE GARD WATERPROOFING MASONRY CONDITIONER AND SEALER - CLEAR

Concrete Gard is a waterproofing masonry conditioner and sealer/primer which penetrates into the pores of concrete.

USES: Use on exterior and interior concrete, stucco, brick, masonry, wood, stone, porous roof tile, asphalt shingles, adobe, plaster, drywall, aluminum siding, vinyl siding and galvanized metal.

SURFACE PREPARATION: Surfaces should be clean and free from grease, oil and dirt.

APPLICATION: Apply by brush, roller or spray. Can also be applied with a garden-type sprayer. It goes on as a milky liquid and dries to a clear film. Dry time is 1-2 hours depending on relative humidity and temperature. Can be top-coated as soon as it is thoroughly dry, generally 1-2 hours. **Concrete block:** Apply two coats. If spraying, backroll the second coat. **Concrete Slabs:** New - may be applied to damp concrete to act as a membrane to aid the curing process. **Existing concrete floors:** Apply one coat only. Aids in keeping the dust down. Do not build up a thick film. **Brick:** Apply two heavy coats, backrolling the second coat. **Vinyl and Aluminum siding:** Apply one or two coats. Rejuvenates the appearance of old siding. Also helps to bond chalky surfaces.

280-90

PRODUCT SPECIFICATIONS

| | |
|-------------------------------------|--|
| <u>COLOR:</u> | Clear only |
| <u>60° GLOSS:</u> | 60 min |
| <u>85° SHEEN:</u> | Medium |
| <u>VEHICLE:</u> | Acrylic resin emulsion |
| <u>SOLVENT:</u> | VOC 218g/L; 1.81 lbs/gal. |
| <u>FLAMMABILITY:</u> | Not applicable |
| <u>% SOLIDS (WEIGHT):</u> | 10.5 - 11.5 |
| <u>VISCOSITY:</u> | Low (35-45 seconds, #2 Zahn Cup) |
| <u>THEORETICAL COVERAGE:</u> | One dry mil @ 160 square feet/gallon |
| <u>RECOMMENDED COVERAGE:</u> | 300 to 400 square feet per gallon depending on porosity of surface |
| <u>WEIGHT PER GALLON:</u> | 8.4 lbs. |
| <u>DRY, SET TO TOUCH:</u> | 3 minutes |
| <u>DRY HARD:</u> | 4 -6 hours (recoat) |
| <u>CLEAN UP SOLVENT:</u> | Warm. soapy water |
| <u>TINTING:</u> | Tinting not recommended |