

382-80 PREP TRANSPARENT LATEX SEALER

382-80 Wall Prep is a transparent latex sealer specially designed for use as a pre-coat on walls which are to be covered with paper or vinyl wallcoverings. It imparts dry strippability to these wallcoverings and greatly reduces damage to the underlying surface.

USES: Clear sealer for painted walls to be used prior to wallpapering.

MATERIAL PREPARATION: Use as is. Thin sparingly with clean water if necessary.

SURFACE PREPARATION: All surfaces must be cleaned of all dirt, dust, wax and grease. Remove all water soluble coatings such as glue size and calcimine. Prime uncoated patching plaster or joint cement with suitable primer on this product.

APPLICATION: Brush, roller or spray. Wall Prep 1 is tinted slightly blue to assist full coverage and film uniformity. Ventilate well during and after application to hasten dry time. Do not use when wall or room temperature is less than 50°F.

382-80

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	Transparent with a slight blue tint
<u>60° GLOSS:</u>	5-15 range
<u>85° SHEEN:</u>	20-40 range
<u>VEHICLE:</u>	Unmodified acrylic resin
<u>PIGMENTATION:</u>	None
<u>SOLVENT:</u>	Water. VOC 78g/L; 0.65 lbs/gal.
<u>FLAMMABILITY:</u>	N/A
<u>% VEHICLE SOLIDS (WEIGHT):</u>	22
<u>% PIGMENT (WEIGHT):</u>	0
<u>% SOLVENT (WEIGHT):</u>	79
<u>% TOTAL SOLIDS (WEIGHT):</u>	22
<u>% TOTAL SOLIDS (VOLUME):</u>	20
<u>VISCOSITY:</u>	75+82 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=1.1 dry mils 400 sq.ft/gal=4.0 wet mils=0.8 dry mils 500 sq.ft/gal=3.2 wet mils=0.6 dry mils
<u>RECOMMENDED COVERAGE:</u>	300-500 square feet depending on surface
<u>WEIGHT PER GALLON:</u>	8.5 lbs.
<u>DRY, SET TO TOUCH:</u>	15-30 minutes
<u>DRY HARD:</u>	Two hours (wait at least 2 hours before hanging wallcoverings.)
<u>CLEAN UP SOLVENT:</u>	Soapy water
<u>TYPE OF CURE:</u>	Water evaporation and coalescence
<u>TINTING:</u>	Universal colorants