

635-SERIES PRO FINISH LATEX VELVET EGGSHELL

This Latex Velvet Eggshell is recommended for high traffic areas or other areas where good washability and scrub resistance is required. This product has good hide and dries quickly to a "smooth" eggshell finish with minimum angular sheen. This line of products is characterized by excellent application properties - brush, spray or roller (low spatter) and is recommended for high production finishing operation.

USES: New and repaint work on interior walls and ceilings made of plaster, drywall, concrete block, etc. On commercial structures where high speed finishing is desired.

MATERIAL PREPARATION: Mix well before using. Thinning not recommended. If necessary, use clean water sparingly.

SURFACE PREPARATION: Previously painted surfaces should be washed with a strong detergent and water to completely remove all dirt, grease, oil and wax. Glossy surfaces should be scuff sanded. All peeling or blistered paint should be removed and primed with wall primer (plaster or drywall), enamel undercoater (wood) or metal primer (metal). Repair all cracks and nail holes with patching plaster, sand smooth and prime with wall primer.

APPLICATION: Do not use when room or wall temperature is less than 50°F. Apply by brush, roller or spray. Apply full even coats and always work toward a wet edge.

AIRLESS SPRAY: Use airless spray equipment capable of maintaining 80-100 lbs. Input pressure with a 28:1 or 30:1 airless pump. Use 17 to 31 thou tips. Output rate will vary with tip size and number of guns in operation.

635-series

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White & colors
<u>60° GLOSS:</u>	5-10
<u>85° SHEEN:</u>	10-20 (very low)
<u>VEHICLE:</u>	Vinyl acetate/acrylic copolymer resin emulsion
<u>PIGMENTATION:</u>	Titanium dioxide and calcium carbonate. All pigments are free of heavy metals and toxic materials.
<u>SOLVENT:</u>	Water and glycols. VOC 88g/L; 0.73 lbs/gal.
<u>FLAMMABILITY:</u>	Not applicable
<u>% VEHICLE SOLIDS (WEIGHT):</u>	17.5
<u>% PIGMENT (WEIGHT):</u>	25
<u>% SOLVENT (WEIGHT):</u>	57.5
<u>% TOTAL SOLIDS (WEIGHT):</u>	42.5
<u>% TOTAL SOLIDS (VOLUME):</u>	29
<u>VISCOSITY:</u>	100-105 KU
<u>THEORETICAL COVERAGE:</u>	533 sq.ft/gal=3 wet mils=0.9 dry mils 400 sq.ft/gal=4 wet mils=0.6 dry mils 320 sq.ft/gal=5 wet mils=0.5 dry mils
<u>RECOMMENDED COVERAGE:</u>	350-400 square feet per gallon (4 wet mils)
<u>WEIGHT PER GALLON:</u>	10.3 lbs.
<u>DRY, SET TO TOUCH:</u>	30 minutes
<u>DRY HARD:</u>	2 hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Warm, soapy water
<u>TYPE OF CURE:</u>	Coalescence
<u>TINTING:</u>	Universal colorants