

645-99 PRO FINISH ANTI-SPATTER LATEX CEILING PAINT

645-99 Pro Finish Latex Ceiling is a high hiding, bright white matte finish designed to meet the requirements for quality finished ceilings. The high build properties and the zero sheen level of the dried film combine to give ceilings a uniform appearance showing no roller marks or surface imperfections. This product has virtually no spatter with roller application. This product is a low VOC formulation. Also this product embodies the physical characteristics necessary to maintain the sound absorption properties of acoustical materials.

USES: All ceilings made of plaster, drywall, cement, etc.

MATERIAL PREPARATION: Mix before using. Thin sparingly with clean water if necessary.

SURFACE PREPARATION: Remove all dirt, grease, wax and wallpaper paste from previously painted surfaces. Degloss glossy or hard surfaces. Remove and repair all peeling or blistered paint and prime with wall primer. Repair all cracks and countersunk nails with patching plaster and prime. Seal water soluble stains with suitable stain blocking primer.

APPLICATION: Do not use when room or wall temperature is less than 50°F. Apply by brush, roller or spray. Apply full even coats and always work towards a wet edge.

AIRLESS SPRAY: Use airless spray equipment capable of maintaining 80-100 lbs. Input pressure with a 28:1 or 30:1 airless pump. Use 17 to 31 thou tips. Output rate will vary with tip size and number of guns in operation.

645-99

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White
<u>60° GLOSS:</u>	0-3 (dead flat)
<u>85° SHEEN:</u>	Less than 4
<u>VEHICLE:</u>	Vinyl acetate/acrylic copolymer resin emulsion
<u>PIGMENTATION:</u>	Titanium dioxide, calcium carbonates and EPA approved silicates. All pigments are free of heavy metals and toxic materials.
<u>SOLVENT:</u>	Water and glycols. VOC 144g/L; 1.20 lbs/gal.
<u>FLAMMABILITY:</u>	Not applicable
<u>% VEHICLE SOLIDS (WEIGHT):</u>	11
<u>% PIGMENT (WEIGHT):</u>	40
<u>% SOLVENT (WEIGHT):</u>	51
<u>% TOTAL SOLIDS (WEIGHT):</u>	49
<u>% TOTAL SOLIDS (VOLUME):</u>	31
<u>VISCOSITY:</u>	105-110 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=1.6 dry mils 400 sq.ft/gal=4.0 wet mils=1.3 dry mils 500 sq.ft/gal=3.2 wet mils=1.0 dry mils
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	11.3 lbs.
<u>DRY, SET TO TOUCH:</u>	One hour
<u>DRY HARD:</u>	Four hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Warm, soapy water
<u>TYPE OF CURE:</u>	Coalescence
<u>TINTING:</u>	Universal colorants