

## **670-00 PRO FINISH ERASER SB QUICK DRY STAIN BLOCKER**

A specially formulated pigmented sealer containing acrylic fortified resins which seal stains on interior and exterior surfaces. Finish coats of latex or solvent based products can be applied within the hour. **Exterior** - For use on small stained areas and for spot priming of bare areas, such as trim, windows, doors, etc. **Do not use on large areas of exterior wood surfaces.**

**USES:** To block out smoke and other water soluble stains on ceiling tile, drywall, plaster, wood, hardboard, etc. Also effective with lipstick, ballpoint ink, crayon, tannin stains in cedar and redwood.

**MATERIAL PREPARATION:** Stir thoroughly before use.

**SURFACE PREPARATION:** Surface must be dry and cleaned of all dirt, dust, chalk, oil and grease. Heavily soiled areas should be washed with a strong detergent, rinsed and allowed to dry thoroughly.

**APPLICATION:** Brush, roller or spray. Allow adequate ventilation during use. Keep away from all heat, pilot lights, sparks and flame. Do not use in temperatures less than 40°F.

**AIRLESS SPRAY:** Recommended fluid pressure of 1600 to 2000 psig; fluid orifice size 0.015 to 0.021.

670-00

**PRODUCT SPECIFICATIONS**

<b><u>COLOR:</u></b>	White
<b><u>60° GLOSS:</u></b>	4 max.
<b><u>85° SHEEN:</u></b>	Low
<b><u>VEHICLE:</u></b>	Soya alkyd resin
<b><u>PIGMENTATION:</u></b>	Titanium dioxide, calcium carbonate and magnesium silicate. All pigments are free of heavy metals and toxic materials.
<b><u>SOLVENT:</u></b>	VMP Naphtha and mineral spirits. VOC meets regulation of 450g/L; 3.80 lbs/gal.
<b><u>FLAMMABILITY:</u></b>	50-55°F - Flammable
<b><u>% VEHICLE SOLIDS (WEIGHT):</u></b>	15
<b><u>% PIGMENT (WEIGHT):</u></b>	57
<b><u>% SOLVENT (WEIGHT):</u></b>	28
<b><u>% TOTAL SOLIDS (WEIGHT):</u></b>	72
<b><u>% TOTAL SOLIDS (VOLUME):</u></b>	47.6
<b><u>VISCOSITY:</u></b>	80-85 KU
<b><u>THEORETICAL COVERAGE:</u></b>	300 sq.ft/gal=5.3 wet mils=2.5 dry mils 400 sq.ft/gal=4.0 wet mils=2.0 dry mils
<b><u>RECOMMENDED COVERAGE:</u></b>	400 square feet per gallon
<b><u>WEIGHT PER GALLON:</u></b>	11.7 - 12.0 lbs.
<b><u>DRY, SET TO TOUCH:</u></b>	10-15 minutes
<b><u>DRY HARD:</u></b>	Two hour (recoat)
<b><u>CLEAN UP SOLVENT:</u></b>	Paint thinner
<b><u>TYPE OF CURE:</u></b>	Oxidation
<b><u>TINTING:</u></b>	Universal colorants