

## **813-75 WOOD STAIN – CLEAR BASE**

Interior wood stain for new wood or wood from which previous finish has been completely removed and surface well sanded.

**USES:** For **interior** use on furniture, panels, woodwork, trim, doors and floors. This product provides the ideal color base coat for subsequent finish coats of gloss or satin finishes.

**MATERIAL PREPARATION:** Hand stir thoroughly before use.

**SURFACE PREPARATION:** **NEW WORK** – Surface must be clean, dry and dust free. Apply stain in an even thin application in the direction of the grain. Brush or wipe out thoroughly. Do not puddle. It is natural for any stain to vary in effect depending on color, porosity and wood grain. Test wood sample before attempting main job. If a darker tone is desired, apply a second coat after first coat is dry. **OLD WORK** – All old finish and stain must be removed and surface well sanded before application of stain – then follow directions for new work as above.

**APPLICATION:** Do not use when temperature is less than 50°F. Apply by brush, foam brush, pad applicator or spray. Apply thin even coats, work with the grain and keep a wet edge.

813-75

**PRODUCT SPECIFICATIONS**

<b><u>COLOR:</u></b>	Clear
<b><u>VEHICLE:</u></b>	Alkyd resin solution
<b><u>PIGMENTATION:</u></b>	Non-crystalline silica
<b><u>SOLVENT:</u></b>	Rule 66 low mineral spirits. VOC meets regulation of 550g/L; 4.59 lbs/gal.
<b><u>FLAMMABILITY:</u></b>	105°F
<b><u>% SOLIDS (WEIGHT):</u></b>	40
<b><u>% SOLIDS (VOLUME):</u></b>	31.9
<b><u>VISCOSITY:</u></b>	Water thin
<b><u>WEIGHT PER GALLON:</u></b>	7.52 lbs.
<b><u>DRY:</u></b>	2-4 hours (will vary with temperature & humidity)
<b><u>CLEAN UP SOLVENT:</u></b>	Paint thinner
<b><u>TINTING:</u></b>	Universal colorants
<b><u>RECOAT:</u></b>	4-6 hours (will vary with temperature and humidity)