

870-00 ACRYPLEX #4 STAIN SEALER

A specially formulated pigmented sealer containing fast drying resins which seal stains on interior and exterior surfaces. Finish coats of latex or solvent based products can be applied within the hour.

USES: To block out smoke and other water soluble stains on ceiling tile, drywall, plaster, wood, hardboard, etc. Also effective with lipstick, ballpoint ink, crayon, tannin stains in cedar and redwood.

MATERIAL PREPARATION: Stir thoroughly before use.

SURFACE PREPARATION: Surface must be dry and cleaned of all dirt, dust, chalk, oil and grease. Heavily soiled areas should be washed with a strong detergent, rinsed and allowed to dry thoroughly.

APPLICATION: Brush, roller or spray. Allow adequate ventilation during use. Keep away from all heat, pilot lights, sparks and flame. Do not use in temperatures less than 40°F.

AIRLESS SPRAY: Recommended fluid pressure of 1600 to 2000 psig; fluid orifice size 0.015 to 0.021.

870-00

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White
<u>60° GLOSS:</u>	10 max.
<u>85° SHEEN:</u>	Low
<u>VEHICLE:</u>	Soya alkyd resins
<u>PIGMENTATION:</u>	Titanium dioxide, silicates and non-crystalline silica.
<u>SOLVENT:</u>	VMP Naphtha and mineral spirits. VOC meets regulation of 450g/L; 3.80 lbs/gal.
<u>FLAMMABILITY:</u>	50-55°F - Flammable
<u>% VEHICLE SOLIDS (WEIGHT):</u>	21
<u>% PIGMENT (WEIGHT):</u>	47
<u>% SOLVENT (WEIGHT):</u>	32
<u>% TOTAL SOLIDS (WEIGHT):</u>	68
<u>% TOTAL SOLIDS (VOLUME):</u>	46
<u>VISCOSITY:</u>	75-80 KU
<u>THEORETICAL COVERAGE:</u>	300 sq.ft/gal=5.3 wet mils=2.4 dry mils 400 sq.ft/gal=4.0 wet mils=1.8 dry mils
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	10.7 - 11.0 lbs.
<u>DRY, SET TO TOUCH:</u>	10-15 minutes
<u>DRY HARD:</u>	One hour (recoat)
<u>CLEAN UP SOLVENT:</u>	Paint thinner
<u>TYPE OF CURE:</u>	Oxidation
<u>TINTING:</u>	Universal colorants