

895-SERIES CERAMIC AQUA BORNE INTERIOR FLOOR FINISH

This floor paint is a versatile interior/exterior product designed to provide protection to all masonry surfaces. The hard, smooth satin finish, which contains ceramic microspheres, makes it particularly effective on floors. Mold and mildew find it difficult to get a foothold. These hard impervious spheres also resist dirt and stains and promote washing. The resistant 100% acrylic resins provide many years of service. Exceptionally easy to apply.

USES: Great for all concrete floors. On all interior and exterior masonry surfaces. Concrete, precast concrete, concrete blocks, cinder block, stucco, plaster literally any masonry surface. Great for basement walls both above and below grade. Use on interior wood floors, stairs and railings. Not recommended for garage floors or exterior wood porches or decks.

MATERIAL PREPARATION: Mix well before use.

SURFACE PREPARATION: Floors and other surfaces to be painted must be cleaned of dirt, mildew, grease, oil, chalk and wax. Sand glossy surfaces. Prime new interior woodwork and trim with enamel undercoat and scuff sand. New wallboard should be primed with primer sealer. New concrete floors should age 30 days, be acid etched and rinsed thoroughly. Cement or cinder blocks can be filled with masonry block filler for best appearing work.

APPLICATION: Do not use when temperature is less than 50°F. Avoid painting in hot, direct sun or in conditions of extreme humidity. Apply by brush, roller or spray. Apply full even coats and always work to a wet edge.

895-series

PRODUCT SPECIFICATIONS

<u>COLOR:</u>	White, Black, Colors and Bases
<u>60° GLOSS:</u>	15-25
<u>85° SHEEN:</u>	20-40 range
<u>VEHICLE:</u>	100% acrylic resin
<u>PIGMENTATION:</u>	Titanium dioxide, ceramic microspheres and/or other fade resistant factory ground pigments. All pigments are free of heavy metals and toxic materials.
<u>SOLVENT:</u>	Water and glycols. VOC 128g/L; 1.06 lbs/gal.
<u>FLAMMABILITY:</u>	Not applicable
<u>% VEHICLE SOLIDS (WEIGHT):</u>	21 (895-49)
<u>% PIGMENT (WEIGHT):</u>	28
<u>% SOLVENT (WEIGHT):</u>	51
<u>% TOTAL SOLIDS (WEIGHT):</u>	49
<u>% TOTAL SOLIDS (VOLUME):</u>	35.8
<u>VISCOSITY:</u>	75-80 KU
<u>THEORETICAL COVERAGE:</u>	One dry mil (3 wet mils) will cover 547 square feet per gallon
<u>RECOMMENDED COVERAGE:</u>	400 square feet per gallon
<u>WEIGHT PER GALLON:</u>	10.4 - 10.8 lbs.
<u>DRY, SET TO TOUCH:</u>	30 minutes
<u>DRY HARD:</u>	Two to four hours (recoat)
<u>CLEAN UP SOLVENT:</u>	Warm soapy water
<u>TYPE OF CURE:</u>	Universal colorants only