

## **942-00 WALL PREP PIGMENTED LATEX SEALER**

942-00 Wall Prep is a pigmented, white latex primer-sealer intended for use over unsealed interior walls. It serves as an excellent prime coat for subsequent coats of oil baser or latex paint and is also a pre-coat for walls to be covered with paper or vinyl wall coverings. Wall Prep 2 imparts dry strippability to wall coverings and greatly reduces damage to the underlying surface. Excellent for new construction.

**USES:** Primer for interior plaster or drywall. Release coat for paper or vinyl wall coverings.

**MATERIAL PREPARATION:** Ready to use from the can; thin sparingly with water if necessary. Mix well before use.

**SURFACE PREPARATION:** Remove all grease, oil or wax by washing with strong detergents and water. Fill all nail holes and tape joints with patching plaster or joint cement and sand smooth. Clean off dust from these patched areas and spot prime with this product. Apply a full coat after dry.

**APPLICATION:** Mix well before use. Do not use when wall or room temperature is less than 50°F. Paint is ready to use from the can, no thinning is necessary. Use nylon brush, roller (¼ nap) or spray. Apply full even coats and work to a wet edge. Avoid excessive brushing or rolling.

**AIRLESS SPRAY:** Use airless spray equipment capable of maintaining 80-100 lbs. Input pressure with a 28:1 to 30:1 airless pump. Use .018 to .031 airless tips. Output rate will vary with tip size and number of guns in operation.

942-00

**PRODUCT SPECIFICATIONS**

<b><u>COLOR:</u></b>	White
<b><u>60° GLOSS:</u></b>	5 max
<b><u>85° SHEEN:</u></b>	10-75
<b><u>VEHICLE:</u></b>	Acrylic resin emulsions
<b><u>PIGMENTATION:</u></b>	Titanium dioxide and EPA approved silicates. All pigments are free of heavy metals and toxic materials.
<b><u>SOLVENT:</u></b>	Water and glycols. VOC 159g/L: 1.33 lbs/gal.
<b><u>FLAMMABILITY:</u></b>	Not applicable
<b><u>% VEHICLE SOLIDS (WEIGHT):</u></b>	20
<b><u>% PIGMENT (WEIGHT):</u></b>	26
<b><u>% SOLVENT (WEIGHT):</u></b>	54
<b><u>% TOTAL SOLIDS (WEIGHT):</u></b>	46
<b><u>% TOTAL SOLIDS (VOLUME):</u></b>	33.4
<b><u>VISCOSITY:</u></b>	100-105 KU
<b><u>THEORETICAL COVERAGE:</u></b>	300 sq.ft/gal=5.3 wet mils=1.7 dry mils 400 sq.ft/gal=4.0 wet mils=1.3 dry mils 500 sq.ft/gal=3.2 wet mils=1.0 dry mils
<b><u>RECOMMENDED COVERAGE:</u></b>	300 to 500 square feet depending on surface
<b><u>WEIGHT PER GALLON:</u></b>	10.2 lbs.
<b><u>DRY, SET TO TOUCH:</u></b>	15-30 minutes
<b><u>DRY HARD:</u></b>	2 hours (wait at least 24 hours before hanging wallcoverings).
<b><u>CLEAN UP SOLVENT:</u></b>	Warm soapy water
<b><u>TYPE OF CURE:</u></b>	Water evaporation and coalescence
<b><u>TINTING:</u></b>	Universal colorants